

BENTONE® 38

P1022.1703

OBM Drilling

Product Description

BENTONE® 38 rheological additive is the oil service industry's standard for a high temperature/high pressure performance organoclay. This additive is manufactured with a high efficiency hectorite clay noted for imparting superior heat stability. BENTONE® 38 exhibits an excellent balance of dispersibility and efficiency. BENTONE® 38 performs well in diesels, mineral oils, poly, linear and isomerized alphaolefins and vegetable oil derivative base fluids.

Features and Benefits

Gives superior downhole stability to muds and completion fluids versus conventional organoclays. Delivers high rheology efficiency over a wide range of intermediate and low polarity base fluids including diesels, mineral oils, poly, linear and isomerized alpha olefins. Effectively suspends weighting agents and cuttings.

International Shipping References

Transportation of BENTONE® 38 is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Max Temperature: 400
- Reservoir Compatible: Both
- Category: Viscosifiers
- Sub Category: Wet Process
- Product Tier: Premium
- SG value: 1.7
- Appearance: White fine powder
- Composition: Organically modified hectorite clay
- Specific Gravity: 1.7
- Moisture %: 3 max

Product Function

Viscosifying drilling fluids including: Oil-based drilling muds, Invert emulsion muds, Packer fluids, Completion fluids, Workover fluids Based on: Synthetic Oils, Mineral Oils, Low toxicity oils and fluids, Diesel oil, Crude oil.

Recommended Treatment

The level of use depends on the rheological properties needed, and the base oil being used. Pilot trials are recommended to optimize performance before field use.

Standard Packing

BENTONE® 38 is packaged in 50 lb multiwall paper sack.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.