

BIO BUFFER

P2216.1903

WBM Drilling

Product Description

BIO BUFFER dissolved in fresh water, Sea water or completion brine together with other Enzymes for WBM chemicals to produce treatment fluids for water-based mud damage or acidizing carbonate formations. BIO BUFFER can be used in a wide range of down hole stimulation and completion applications in oil and gas production wells and water and gas injection wells. It is typically used in wells with bottom hole static temperature in the range 20°C - 150°C. It is used to stabilize the enzymes and is particularly useful where medium to high density completion brines are used.

Features and Benefits

For treating drilling mud damage within the reservoir section of open hole wells drilled with water-based muds particularly ones containing CaCO₃ weighing material and or carbonate drill cuttings fines. Soluble in wide range of completion brine types and brine densities. Low environmental impact and high biodegradability.

International Shipping References

Transportation of BIO BUFFER is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Liquid
- Max Temperature: 300
- Reservoir Compatible: Both
- Category: Breakers
- Sub Category: pH Buffer
- Product Tier: Premium
- SG value: 1.15
- Appearance: Clear to Pale yellow liquid
- Flash Point: >100 °C
- Specific Gravity: 1.10 - 1.20
- pH: 3.6 - 5.6

Product Function

BIO BUFFER is used as a buffer agent in conjunction with acetic acid, in the buffering range of pH 3.6 - 5.6.

Recommended Treatment

Typically, 5 – 10 % w/v dissolved in completion brine for most applications lower or higher concentrations can be used. Contact supplier for specific guidance on mud cake breaker formulations for particular applications.

Standard Packing

BIO BUFFER is supplied in 55 gal drums, 5 USG pail

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.