

BIOCIDE 2S

P101.9310

WBM Drilling

Product Description

BIOCIDE™ 2S is a biodegradable triazine based product utilized as a bactericide in drilling, completion, or work over and packer fluids.

Features and Benefits

BIOCIDE™ 2S has a low order of toxicity to marine life and is classified by OCNS under Category E. BIOCIDE™ 2S is easy to utilize and effective at controlling slime and corrosion caused by micro-organisms in drilling, completion, workover and packer fluids. BIOCIDE™ 2S is effective against aerobic and anaerobic bacteria. BIOCIDE™ 2S does not have any affinity for solids; therefore no replenishment is required to offset losses through solids removal equipment.

International Shipping References

Transportation of BIOCIDE™ 2S is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Safety Data Sheet (SDS) for this product prior to use.

Typical Physical Properties

- Physical State: Liquid
- Max Temperature: 300
- Reservoir Compatible: Both
- Category: Biocides
- Sub Category: Triazine
- Product Tier: Regular
- SG value: 1.04
- Appearance: Colorless to pale yellow liquid
- pH (Neat): 10 – 12
- Specific Gravity (25 °C): 1.03 – 1.05
- Bulk Density(Ground), lbs/Ft³: 10

Product Function

BIOCIDE™ 2S is utilized to control sulphate reducing bacteria which can produce harmful corrosion. BIOCIDE™ 2S will protect polymers, which are susceptible to bacterial degradation. BIOCIDE™ 2S may also be utilized to control bacteria in injection waters.

Recommended Treatment

The normal initial treatment for circulating fluids is 0.1–0.3% where an alkaline pH range is being maintained. Higher dosage rates will be required at neutral pH ranges and where no further circulation takes place i.e. packer fluids. Daily maintenance of 10% of initial treatment is recommended for circulating fluids.

Standard Packing

BIOCIDE™ 2S is packaged in 26 kg pail or 55 USG HDPE drum containing 215 kgs net weight.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.