

BITSOL

P535.0207

WBM Drilling

Product Description

BITSOL™ is a special blend of environmentally acceptable ionic and nonionic surfactants designed to prevent sticky drilled cuttings from “balling up” the bit and drill string.

Features and Benefits

BITSOL™ reduces the surface tension on the steel surfaces to prevent the cuttings and wall cake from adhering to the bit and bottom hole assembly. The BITSOL™ surfactant package also has the ability to neutralize the electrostatic charges on the drill string, thereby reducing the attraction the charged clay particles have for the steel surface.

International Shipping References

Transportation of BITSOL™ is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Liquid
- Max Temperature: 300
- Reservoir Compatible: Non-Reservoir
- Category: ROP Enhancers
- Sub Category: Surfactant
- Product Tier: Regular
- SG value: 1
- Appearance: Colourless liquid
- pH (Neat): 5 - 8
- Specific Gravity (25 °C): 0.99 - 1.01
- Flash Point: >100 °C

Product Function

BITSOL™ is utilized to maintain a drill string free of drilled cuttings.

Recommended Treatment

BITSOL™ should be added directly into the mud system to prevent bit balling at a concentration of 0.5–1.0% by volume. If balling does occur it is recommended that a pill containing 2 drums of BITSOL™ in 20 bbls of sea water or fresh water be pumped through the bit. In order to avoid aeration of the mud, the BITSOL™ should be added to the mud system with stirring, not through the mixing hopper.

Standard Packing

BITSOL™ is packaged in 55 USG (208 liters) steel drum containing 210 kgs net weight.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.