

CFL

P405.9503

WBM Drilling

Product Description

CFL (Chrome free lignosulphonate) is a thinner for water base drilling fluids, which conforms to OCMA DFCP 8 specification.

Features and Benefits

CFL is an effective deflocculant in a wide range of water base drilling fluids systems. CFL is effective at temperatures in excess of 150 °C (302°F). CFL provides fluid loss control and acts as an emulsifier of oil in water base drilling fluids.

International Shipping References

Transportation of CFL is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Max Temperature: 302
- Reservoir Compatible: Non-Reservoir
- Category: Defloc./Thinners
- Sub Category: WBM Thinner
- Product Tier: Regular
- SG value: 1.3
- Appearance: Black free flowing powder
- pH (5% solution): 3 - 5
- Bulk Density Kg/m³: 800 - 1000 kg/m³

Product Function

CFL is used to prevent salt flocculation of bentonite and to control rheology in high and low solids salt based drilling fluids. CFL minimizes the effects of high temperature gelation.

Recommended Treatment

Recommended treatment for C F L are generally 0.5–8.0 lbs/bbl (1.4–23.0 kgs/m³) depending upon solids content and degree of salinity. A pH range of at least 9 is required to ensure product solubility and effectiveness.

Standard Packing

CFL is packaged in 25 kgs multiwall paper sack.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.