

ESM D2

P419.1403

WBM Drilling

Product Description

ESM D2 is an acrylic co – polymer Deflocculant developed to offer excellent dispersion of Micromax weighted water – based fluids under HPHT conditions.

Features and Benefits

ESM D2 Stable at temperatures over 230 °c (450?f) ESM D2 Stable at mud weights > 3.0 sg (25 ppg) Resistant to contaminants ESM D2 “Green” HSE profile being non-toxic & environmentally safe

International Shipping References

Transportation of ESM D2 is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Liquid
- Max Temperature: 450
- Reservoir Compatible: Both
- Category: Defloc./Dispersants
- Sub Category: Acrylic Copolymer
- Product Tier: Regular
- SG value: 1
- Appearance: Amber colour liquid
- pH: 4 - 4,5
- Specific Gravity: 1.0

Product Function

ESM D2 Deflocculant for freshwater & brine based drilling & completion fluids. ESM D2 Provides low, controllable rheologies, designed for Micromax weighted fluids able to be used in ultra HPHT environments.

Recommended Treatment

Treatment levels for ESM D2 range General use at 10 -20 gm/litre (3.5-7 ppb). Pilot testing is recommended to determine the optimum concentration for any specific application.

Standard Packing

ESM D2 is packaged in 250 kgs steel drum.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.