

FCL

P401.9303

WBM Drilling

Product Description

FCL (ferrochrome lignosulphonate) is a thinner for water base drilling fluids, which conforms to OCMA DFCP 8 specification.

Features and Benefits

FCL is an effective deflocculant in a wide range of water base drilling fluids systems. FCL is effective at temperatures in excess of 150oC (302oF). FCL provides fluid loss control and acts as an emulsifier of oil in water base drilling fluids.

International Shipping References

Transportation of FCL is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Max Temperature: 302
- Reservoir Compatible: Non-Reservoir
- Category: Defloc./Thinners
- Sub Category:
- Product Tier: Regular
- SG value: 1.1
- Appearance: Dark brown free flowing powder
- pH (1% solution): 3 - 5
- Bulk Density: 570 - 630 kg/m³

Product Function

FCL is used to prevent salt flocculation of bentonite and controls rheology in high, low solids and salt based drilling fluids. FCL minimizes the effects of high temperature gelation.

Recommended Treatment

Recommended treatment for F C L is generally 0.5–8.0 lbs/bbl (1.4–23.0 kgs/m³) depending upon solids content and degree of salinity. A pH range of at least 9 is required to ensure product solubility and effectiveness.

Standard Packing

FCL is packaged in 25 kgs multiwall paper sack.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.