

HEMATITE POWDER API

P1800.1007

WBM/OBM Drilling

Product Description

Hematite Powder is a high quality, ground iron oxide (hematite) utilized as a weighting agent in drilling fluids which meets ANSI/API Specification 13A:18th edition – February 2010 / ISO 13500:2009 Section 8.

Features and Benefits

Hematite Powder is applicable in all types of drilling fluids, including freshwater, seawater and oil-base mud. Hematite Powder is ground to such a particle size that less than 1.5% wt will be more than 75 micro; less than 15% wt will be less than 6 micron and less than 15% wt will be high than 45 micro at a specific gravity of 5.05. Fluids weighted with Hematite contain fewer solids by volume than those weighted with barite, making higher mud weights possible.

International Shipping References

Transportation of Hematite Powder is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Max Temperature: 450
- Reservoir Compatible: Both
- Category: Weighting Agents
- Sub Category: Acid Soluble
- Product Tier: Regular
- SG value: 5.05
- Appearance: Dry red to brown powder
- Specific Gravity: 5.05 min
- Particle Hardness: 5-6 MOHS Scale (1-10)
- Soluble Hardness(As calcium): 100 mg/Kg, Max
- Residue greater than 75 µm: 1.5% maximum mass fraction
- Residue greater than 4,575 µm: 15% maximum mass fraction

Product Function

Hematite Powder can be used to increase the density of all drilling and completion fluids to 25 lb/gal (3.0 SG). It is especially useful in high-density kill fluids.

Recommended Treatment

The quantity of Hematite required can be calculated using the following formula: Hematite, Lb/bbL = $1,750(W2-W1)/41.66-W2$ Where: W1=Initial mud weight in lb/gal W2=Desired mud weight in lb/gal Hematite, Kg/m3 = $5,000(W2 - W1)/5.05 - W2$ Where: W1=Initial mud weight in SG W2=Desired mud weight in SG

Standard Packing

Hematite Powder is packaged in 100-lb (45.4-kg), multiwall paper sacks; and is available in bulk.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.