

IRON-WATE

P1503.9303

WBM/OBM Drilling

Product Description

IRON-WATE™ is high-purity ground refined mineral Hematite/ Iron Oxide (Fe₂O₃). It has a minimum density of 5.0 making it a superior alternative to BARITE for adjusting and maintaining density in all types of drilling fluids.

Features and Benefits

IRON-WATE™ has a density 20% greater than BARITE, which means less usage of weight material and fewer solids for a given density. IRON-WATE™ provides improved rheological properties and the plastic viscosities are 2 – 30% less than the Barite muds. IRON-WATE™ is acid soluble (>95%). IRON-WATE™, due to its lower solids concentration, results in improved penetration rates and decreases in overall drilling fluid cost. IRON-WATE™ will partially scavenge H₂S at neutral and low pH levels and may be regarded as a secondary sulfide scavenger. When IRON WATE™ is used in H₂S areas a high pH should always be maintained.

International Shipping References

Transportation of IRON-WATE™ is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Max Temperature: 450
- Reservoir Compatible: Both
- Category: Weighting Agents
- Sub Category: Acid Soluble
- Product Tier: Regular
- SG value: 5
- Appearance: Reddish/brown to black powder
- Particle Hardness: 5-6 MOHS Scale (1-10)
- Bulk Density Kg/m³: 2200 - 2300

Product Function

IRON-WATE™ is applicable to all drilling fluids for the purpose of increasing and/or maintaining required density. It is excellent for 'kill' fluids having a maximum achievable density of 26 lbs/gal (3121 kgs/m³).

Recommended Treatment

The amount of IRON-WATE™ needed to increase drilling fluid density is calculated as follows: LBS/ BBL : 1750 (W₂– W₁) lbs/(41.66 -W₂)
Where: W₁ = Initial specific gravity W₂= Specific gravity required

Standard Packing

IRON-WATE™ is packaged in 25 kg, 50 kgs, and 100 lbs (45.4 kgs) multiwall paper sacks. It is also available in bulk form in 1 or 1.5 metric ton jumbo bags.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.