

KWIKSPOT - PD

P1326.2002

WBM/OBM Drilling

Product Description

KWIKSPOT – PD is a proprietary powder blend of asphaltic materials, surfactants and clay inhibitors used as spotting chemical in drilling mud system.

Features and Benefits

KWIKSPOT – PD is dispersed in diesel oil or low toxic base oil and it is spotted across the target zone to release stuck pipe. KWIKSPOT – PD contains unique "cake cracking" surfactants which crack and penetrate the filter cake to equalize pressure around differently stuck drilling tools. KWIKSPOT – PD does not require high shear and long mixing time fluids and it will provide the rheological properties required.

International Shipping References

Transportation of KWIKSPOT – PD is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Max Temperature: 350
- Reservoir Compatible: Non-Reservoir
- Category: Spotting Fluids
- Sub Category:
- Product Tier: Regular
- SG value: 1.1
- Appearance: Light gray to black free flowing powder
- Bulk Density: 0.90 - 2.00 g/cc

Product Function

KWIKSPOT – PD is spotting chemical designed and formulated to be dispersed in diesel oil and / or low toxic base oil to release stuck drill pipe over different densities in all drilling wells. KWIKSPOT - PD has been specifically designed containing highly efficient surfactants to penetrate and crack waterbased mud filter cake in order to balance the pressure around stuck drilling pipe and tools. Effective spotting fluid ratio is to be prepared and decided based on the specific type of mixture in order to obtain the required rheology, lubricity coefficient and gel strength. KWIKSPOT – PD is not recommended to be used in production zones.

Recommended Treatment

KWIKSPOT – PD compatible with invert emulsion fluids; it can be incorporated to the system (1–5% w/v concentration). Pilot testing to confirm compatibility is recommended.

Standard Packing

KWIKSPOT - PD is available in 25Kg or 50 Lbs paper sack.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.