

NOCOR 4089

P215.9405

WBM/OBM Drilling

Product Description

NOCOR™ 4089 is an oil soluble/water dispersible film amine which provides protection against the corrosive effects of H₂S, CO₂ and turbulence induced corrosion in producing oil and gas wells.

Features and Benefits

NOCOR™ 4089 provides excellent film persistency which can be applied by batch or continuous treatment. NOCOR™ 4089 can also be used for corrosion control in surface facilities and transmission lines. NOCOR™ 4089 remains effective when operating temperatures exceed 150°C (302°F).

International Shipping References

Regulatory agencies classify NOCOR™ 4089 as combustible liquid with UN 1993 for transportation.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Liquid
- Max Temperature: 302
- Reservoir Compatible: Both
- Category: Corrosion Inhibitors
- Sub Category: Oil Soluble
- Product Tier: Regular
- SG value: 0.85
- Appearance: Dark Brown Liquid
- Specific Gravity (25 °C): 0.80 - 0.90
- Flash Point: > 65 °C

Product Function

NOCOR™ 4089 provides long-term film life to prevent corrosion in producing wells, crude flow lines and gas transmission lines.

Recommended Treatment

NOCOR™ 4089 is normally diluted at a ratio of one part chemical to nine parts or more high aromatic solvent. Producing Wells: Optimum protection will be provided with a batch treatment of 1000 ppm NOCOR 4089. Circulate the oil well for the maximum possible time following inhibitor injection. Continuous treatment with NOCOR 4089 is normally made at 10–25 ppm based on total produced fluid. Transmission Lines: Inject into the oil system continuously 10–50 ppm based on total fluid throughput. Continuous treatment in gas systems consists of adding one pint of the NOCOR 4089 solvent mixture per MMSCF of gas.

Standard Packing

NOCOR™ 4089 is packaged in 55 USG (208 liters) steel drum.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.