

OILVIS II

P1012.0802

OBM Drilling

Product Description

OILVIS™ II is acrylate based synthetic copolymer supplied as a low viscosity emulsion. The emulsion form mixes easily and yields rapidly, simplifying both onshore and offshore handling. It requires less time, energy and equipment to mix than typical amine treated bentonite. It can be used alone or in conjunction with amine treated bentonite.

Features and Benefits

OILVIS™ II generates viscosity quickly and helps in rapid mud replacement in the event of lost circulation. OILVIS™ II acts synergistically with bentonites to give better performance than that of either product alone. Unlike bentonite, viscosity generation is fast, predictable and controllable. OILVIS™ II is compatible with most other additives commonly used in oil based drilling fluids and has a thermal upto 275° F.

International Shipping References

Transportation of OILVIS™ II is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use. OILVIS™ II should be protected from freezing and should be stored between 5 – 35 Deg C

Typical Physical Properties

- Physical State: Liquid
- Max Temperature: 350
- Reservoir Compatible: Non-Reservoir
- Category: Filtration Control
- Sub Category: Viscosifier
- Product Tier: Regular
- SG value: 1
- Appearance: White liquid
- Specific Gravity (20 °C): 1.0
- Flash Point: >250 °C
- pH (1% solution): 2.0 - 5.0
- Ionic nature: Anionic

Product Function

OILVIS™ II will produce a rapid and predictable increase in low shear viscosity in oil based ,invert emulsion drilling fluid. OILVIS™ II will increase the yield point and gel strength of the fluid to provide carrying capacity for cuttings and suspension of the weighing agents. A high gel strength decreases the settling rate of weighting agents, allowing for onshore mixing.

Recommended Treatment

The normal treatment for OILVIS™ II is 2 - 4 lbs/bbl dependent upon solids content of the drilling fluid.

Standard Packing

OILVIS™ II is packaged in 55 USG steel drum containing 200 kgs net.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.