

PETROLIZE CL

P2204.1403

WBM Drilling

Product Description

PETROLIZE CL is Enzyme-based Breaker suitable for biopolymer gels and Filter-cakes in Oilfield boreholes. PETROLIZE CL works at high downhole temperatures. Selective Hydrolysis of Guar results in even breaking action. No reaction with Tubing, Hydrocarbons or Formation components. PETROLIZE CL reduces Acid Consumption in injection wells and increase production. PETROLIZE CL enzyme protein will work between borehole temperatures of 50 to 80 Deg C and pH range of 7 to 9.

Features and Benefits

Throughout the life of the well, PETROLIZE CL usage will ensure an even drainage of entire reservoir and sustained production by controlled hydrolysis of Bio-Polymer. Enzyme Proteins are specific for the Galactomannan of the Guar based filter cake. PETROLIZE CL will not react with the metal surfaces that would increase iron concentrations and result in Sludging and ironprecipitation problems. PETROLIZE CL will not promote corrosion of screens and other downhole components. PETROLIZE CL minimizes well down time as completed well can be placed on-line in much lesser time than conventional acid breakers and cleanup technologies.

International Shipping References

Transportation of PETROLIZE CL is not restricted by any regulatory agency.

Safe Handling Recommendations

Avoid skin and eye contact, inhalation or ingestion. For skin contact, wash with soap and large quantities of water. For eye contact, flush with large quantities of water. Use properly designed respirator if adequate ventilation is not available. Refer to the Material Safety Data Sheet for specific details.

Typical Physical Properties

- Physical State: Liquid
- Max Temperature: 300
- Reservoir Compatible: Reservoir
- Category: Breaker Additives
- Sub Category: Starch Breaker
- Product Tier: Premium
- SG value: 1.1
- Appearance: Medium to dark Amber liquid
- pH: 1% solution in water 6.0 ± 1
- Density: 1.15 – 1.25 g/ml

Product Function

PETROLIZE CL enhances Production by drastically reducing Bio-Polymer cleanup time.

Recommended Treatment

Treatment levels are determined by specified requirements.

Standard Packing

PETROLIZE CL is packaged in 50 kgs polyethylene drums.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.