

PETROSCAL DHT

P785.2301

WBM Drilling

Product Description

PETROSCAL DHT is synthetic polymer specifically designed for high-temperature and /or high-salinity environments.

Features and Benefits

Works well at any salinity. Reduces differential sticking tendencies. Can improve thermal stability of whole mud system. Non-fermenting. Helps maintain the integrity of cuttings. Calcium tolerance in excess of 100,000 ppm.

International Shipping References

Transportation of PETROSCAL DHT is not restricted any regulatory agency.

Safe Handling Recommendations

For specific instruction on handling refer to the SDS.

Typical Physical Properties

- Physical State: Solid
- Max Temperature: 475
- Reservoir Compatible: Both
- Category: Viscosifiers
- Sub Category: High Temperature
- Product Tier: X-Premium
- SG value: 0
- Bulk Density: 0.2 -0.4
- Appearance: White Powder
- Ionic nature: Anionic

Product Function

Provide viscosity on WBM's with any salinity ranges and or environments with BHT up to 475 °F ~ 246 °C.

Recommended Treatment

For HTHP Fluid-loss control use 1 to 5 ppb. For rheology control use 0.5 to 5 ppb. Mix slowly through conventional jet hopper.

Standard Packing

PETROSCAL DHT is presented in 10 kg sacks or 300 kg Big Bags.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.