

SIZED CALCIUM CARBONATE

P8001.2201

WBM/OBM Drilling

Product Description

Sized Calcium Carbonate is available in PPC in five grades: 2, 5, 10, 25 and 50.

Features and Benefits

Fully soluble in 15% HCl solution (1 gal of HCl dissolves 1.84 lb of Calcium Carbonate). Provides effective bridging

International Shipping References

Transportation of this product is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Use of appropriate respirator, gloves, goggles and apron is recommended for employee comfort and protection. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Max Temperature: 500
- Reservoir Compatible: Both
- Category: Weighting Agents
- Sub Category: Acid Soluble
- Product Tier: Regular
- SG value: 2.6
- Appearance: White powder.
- Specific Gravity: 2.6.
- Soluble in HCL: 99% minimum.

Product Function

Increase the density of water based and oil based muds. Increase the density of brine fluids. Bridge formation for fluid loss control.

Recommended Treatment

Use the following formulas to determine the appropriate concentrations to be added: 1. As a weighting agent, add as much product as needed to increase fluid density up to 14lb/gal (1.68gm/cm³) For 1 bbl starting volume $X=945 (WF - W1) / (22.5 - WF)$ For 1 bbl final Volume $X=945 (WF - W1) / (22.5 - W1)$ Where, X = SIZED CALCIUM CARBONATE required, lb/bbl WF= Final desired mud Weight, lb/gal W1 = Initial mud weight, lb/gal 2. As a bridging agent, add 5,10 lb/bbl (14.26 – 28.53 kg/m³) of the appropriate grades of the product

Standard Packing

The product is packaged in 25 kgs, 50 kgs multiwall paper sacks with polyethylene liner or 1 - 1.5 MT Big Bags.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.