

SODIUM BICARBONATE

P1611.9305

WBM/OBM Drilling

Product Description

SODIUM BICARBONATE (NaHCO_3) is utilized to precipitate soluble calcium in water base drilling fluids. It is used primarily for treating cement contaminated drilling fluids.

Features and Benefits

SODIUM BICARBONATE provides two basic functions: (1) removes soluble calcium (2) lowers pH of the drilling mud

International Shipping References

Transportation of SODIUM BICARBONATE is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Max Temperature: 300
- Reservoir Compatible: Both
- Category: Commercial
- Sub Category:
- Product Tier: Regular
- SG value: 2.159
- Appearance: White crystalline free flowing powder
- Purity: 99 min
- pH (1% solution): 8.0 - 8.8
- Bulk Density Kg/m^3 : 850 - 900

Product Function

SODIUM BICARBONATE should be mixed through the mud hopper. Do not use Sodium Bicarbonate to treat make-up water. Use Soda Ash for softening water, over treatment with Sodium Bicarbonate will result in carbonate / bicarbonate contamination of the drilling fluid resulting in rheological and filtration control problems.

Recommended Treatment

Pretreatment with 0.25–0.5 lbs/bbl (0.7–1.4 kgs/m^3) of Sodium Bicarbonate as a precaution before drilling out cement. When “green” cement is drilled, the treatment with Sodium Bicarbonate may need to be doubled or even tripled. Bicarbonates of soda will result in decrease in pH, allowing the calcium solubility to increase.

Standard Packing

SODIUM BICARBONATE is packaged in 25 kgs or 50 kgs multiwall paper and polyethylene liner sack.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.