

SODIUM CHLORIDE

P1612.9305

WBM/OBM Drilling

Product Description

SODIUM CHLORIDE is commonly referred to as SALT and is used for making clear Brines for work over and completion fluids.

Features and Benefits

SODIUM CHLORIDE is used in drilling fluids and brine form as a completion or workover fluid to a maximum density of 10 lb/gal (1.20 SG). SODIUM CHLORIDE restricts shale hydration by decreasing the water activity. SODIUM CHLORIDE reduces the potential of forming gas hydrates in deep water drilling.

International Shipping References

Transportation of SODIUM CHLORIDE is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Use of appropriate respirator, gloves, goggles and apron is recommended for employee comfort and protection. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Max Temperature: 300
- Reservoir Compatible: Both
- Category: Dry Salts
- Sub Category:
- Product Tier: Regular
- SG value: 1.26
- Appearance: White free flowing granular powder
- Purity: > 99.0 %
- Specific Gravity: 1.26
- Solubility (Water): 35.7 gm/100 @ 20 °C

Product Function

SODIUM CHLORIDE is used to increase the density and shale inhibition in water based drilling fluids. SODIUM CHLORIDE reduces the freezing point and gas hydration in water and oil base muds.

Recommended Treatment

Add 352 kg of SODIUM CHLORIDE to 1 m³ of water to get a maximum density of 1.20.

Standard Packing

SODIUM CHLORIDE is packaged in 25 kg multi wall paper sacks or in 1MT jumbo bag.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.