

TRUFOAM AS

P536.0204

WBM Drilling

Product Description

TRUFOAM™ AS is an amphoteric surfactant that provides stable foams in water and acid at elevated temperatures.

Features and Benefits

? Excellent acid foaming agent ? Temperature stable above 212OF (100OC) ? Does not break down in HCl at higher temperatures ? Suspends solid particles and fines ? Does not plate out on the pipe or formation ? Tolerant to brine and crude

International Shipping References

Transportation of TRUFOAM™ AS is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Liquid
- Max Temperature: 212
- Reservoir Compatible: Non-Reservoir
- Category: Foaming Agents
- Sub Category: Amphoteric Surfactant
- Product Tier: Premium
- SG value: 1.02
- Appearance: Yellow liquid
- Activity %: 45 %
- pH (Neat): 5 - 7
- Specific Gravity (25 ?C): 1.00 - 1.03
- Flash Point: >100 ?C
- Texture: Semi-floppy, Semi-stiff

Product Function

TRUFOAM™ AS contains organic molecules whose ionic charges depend on the pH of the fluid. As the pH rises, the charge changes from cationic to nonionic to anionic. This change in pH helps to enhance flow-back after the acid job because anionic surfactants leave sandstones "water-wet". TRUFOAM AS can be used in well clean-out operations because the foamed acid is more readily recovered from wells, especially those with depleted bottom hole pressures. TRUFOAM AS works in the presence of all oil field brines and is tolerant of clay fines, crude oil and condensate.

Recommended Treatment

The recommended concentration for TRUFOAM™ AS is 1–5 gal/1000 gallons (1–5 L/m³) as a surfactant and 5–15 gal/1000 gallons (5–15 L/m³) as a foamer.

Standard Packing

TRUFOAM™ AS is packaged in HDPE drum containing 200 kgs net.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.