

TRULOSE 100

P746.9806

WBM Drilling

Product Description

TRULOSE™ 100 is a modified cross linked potato starch polymer which is used to control fluid loss in high temperature water base drilling fluids.

Features and Benefits

TRULOSE™ 100 will provide fluid loss control over a wide pH range and is resistant to divalent ion contamination. TRULOSE™ 100 is temperature resistant to at least 135°C (275°F). TRULOSE™ 100 is readily dispersible and can be added rapidly through the mixing hopper. TRULOSE™ 100 is not susceptible to bacterial degradation.

International Shipping References

Transportation of TRULOSE™ 100 is not restricted by any regulatory body

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Max Temperature: 275
- Reservoir Compatible: Both
- Category: Filtration Control
- Sub Category: Starches
- Product Tier: Regular
- SG value: 1.5
- Appearance: Off-white free flowing powder
- pH (1% solution): 7 - 10
- Bulk Density Kg/m³: 600 - 800

Product Function

TRULOSE™ 100 is utilized as a fluid loss reducer in all types of water base drilling fluids and is effective in both fresh and saline environment.

Recommended Treatment

Treatment levels for TRULOSE™ 100 are generally in the range 2.0 – 8.0 lbs/bbl (5.7–22.8 kgs/m³) The actual concentration used will depend upon the type of drilling fluids being treated.

Standard Packing

TRULOSE™ 100 is packaged in 25 kgs multiwall paper sack with polyethylene coating.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.