

## TRUPAC R

P714.9305

WBM Drilling

### Product Description

TRUPAC™ R is a purified high molecular weight polyanionic cellulose polymer which provides filtration control and viscosity to water base drilling fluids.

### Features and Benefits

TRUPAC™ R provides supplementary viscosity and reduce filtration rate in fresh water and salt based drilling fluids. TRUPAC™ R is effective over a wide pH range and has a high tolerance to contamination. TRUPAC™ R has a strong affinity for clay surfaces and will restrict their hydration and dispersion. TRUPAC™ R is not susceptible to bacterial degradation. TRUPAC™ R has shown to be effective in field applications at bottom hole temperatures up to 300 °F (149°C).

### International Shipping References

Transportation of TRUPAC™ R is not restricted by any regulatory agency.

### Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

### Typical Physical Properties

- Physical State: Solid
- Max Temperature: 300
- Reservoir Compatible: Non-Reservoir
- Category: Filtration Control
- Sub Category: Polyanionic Cellulose
- Product Tier: Regular
- SG value: 1.5
- Appearance: Off-white free flowing powder
- pH (1% solution): 7 - 10
- Bulk Density Kg/m<sup>3</sup>: 600 - 900

### Product Function

TRUPAC™ R is cost effective means of controlling fluid loss and increasing viscosity and improve quality of filter cake in water base drilling fluid systems.

### Recommended Treatment

TRUPAC™ R concentrations in the range of 0.5–2.0 lbs/bbl (1.43–5.71 kgs/m<sup>3</sup>) are required to control filtration rate. Addition must be made slowly and evenly through a hopper at rate of 10–20 minutes every 25 kgs sack.

### Standard Packing

TRUPAC™ R is packaged in 25 kgs multiwall paper sack.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS  
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.