

TRUPAC SL

P758.0204

WBM Drilling

Product Description

TRUPAC™ SL is a premium grade low molecular weight polyanionic cellulose polymer which provides filtration control to water based drilling fluids.

Features and Benefits

TRUPAC™ SL provides filtration control and stabilizes the rheological properties of most water base drilling fluids. TRUPAC™ SL provides fluid loss control and gives low plastic viscosity values when added to the drilling fluid. TRUPAC™ SL is effective in fresh water and salt based fluids and at low concentrations has the ability to reduce the rheology of flocculated and high solids fluids. TRUPAC™ SL has a strong affinity for clay surfaces and will restrict their hydration and dispersion. TRUPAC™ SL is not susceptible to bacterial attack and resistant to common contaminants. TRUPAC™ SL has shown to provide stable filtration control at bottom hole temperatures in excess of 300°F (149°C). TRUPAC™ SL has a high tolerance to divalent ions and is effective over a wide pH range.

International Shipping References

Transportation of TRUPAC™ SL is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Max Temperature: 300
- Reservoir Compatible: Both
- Category: Filtration Control
- Sub Category: Polyanionic Cellulose
- Product Tier: Regular
- SG value: 1.5
- Appearance: Off-white free flowing powder
- pH (1% solution): 7 - 8
- Bulk Density Kg/m³: 500 - 800

Product Function

TRUPAC™ SL provides superior fluid loss control in most water base drilling fluid system with minimum or no effect on viscosity.

Recommended Treatment

Concentrations in the range of 0.25–3.0 lbs/bbl (0.7–8.6 kgs/m³) are required to maintain filtration control with TRUPAC™ SL. The actual treatment will depend upon the composition of the drilling fluid and drilling conditions encountered.

Standard Packing

TRUPAC™ SL is packaged in 25 kgs multiwall paper sack.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.