

TRUPLUG

P824.0502

WBM Drilling

Product Description

TRUPLUG is an acid soluble materials used as the base of TRUPLUG system, primarily used to cure extreme lost circulation.

Features and Benefits

TRUPLUG is fully acid soluble, non hazardous, non toxic and biodegradable. It does not require specialized rig equipment for mixing. TRUPLUG is blend of milled borate salt and selected polymers that can be used at high temperature of up to 400° F (204° C). All components are of low particle size that can be safely pumped through mud motors, logging tools and other downhole equipment.

International Shipping References

Transportation of TRUPLUG is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Max Temperature: 400
- Reservoir Compatible: Non-Reservoir
- Category: LCM
- Sub Category: Crosslink LCM
- Product Tier: Regular
- SG value: 1.9
- Appearance: Free flowing product
- pH (10% solution): 7 - 8
- Bulk Density Kg/m³: 2

Product Function

TRUPLUG is pumped as a viscosified fluid to the loss zone where it sets up as a rigid, yet relatively soft and easily drilled out. The density can be adjusted with barite or other inert weighting agent. The mixed TRUPLUG system, with or without weighting agent can be held as a premix in advance of using. In hotter climates it may be necessary to add a biocide.

Recommended Treatment

TRUPLUG is used at 100 lb/bbl. Add TRUPLUG through mixing hopper at 2–3 minutes per 50 lb sack. Volume of pill normally range from 50–120 bbls depends on hole sizes. TRUPLUG should be mixed in water or recommended non–calcium brine.

Standard Packing

TRUPLUG is packaged in 50 lbs multiwall paper sack.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.