

TRUZAN DS L
WBM Drilling

Product Description

TRUZAN DS - L is a high-purity Xanthan gum biopolymer, suspended in an ultra-clean mineral oil.

Features and Benefits

- TRUZAN DS – L Provides good suspension properties restricting the settlement of weighting agents and drilled cuttings. - TRUZAN DS - L is shear thinning and promotes low bit viscosity needed to maximize penetration rates, and high annular viscosity to ensure effective hole cleaning. - TRUZAN DS - L is stable over a wide pH range and its effective in saturated brines as well as fresh and sea water base drilling fluids. - TRUZAN DS – L provides excellent friction reduction for coiled tubing operations. - TRUZAN DS - L was the first truly stable thickener for hydrochloric acid used in the oilfield. The Liquid Xanthan Gum suspension is uniquely stable, easily handled and useful in both oilfield and non-oilfield applications

International Shipping References

Transportation of TRUZAN DS – L is not restricted by any regulatory agency.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Liquid
- Max Temperature: 300
- Reservoir Compatible: Both
- Category: Viscosifiers
- Sub Category: Liquid Xanthan Gum
- Product Tier: X-Premium
- SG value: 1.1
- Appearance: Light tan liquid with slight odor
- Activity %: 42
- Thermal Stability: 121 °C/ 250 °F
- pH (1% solution): 6 -8
- Specific Gravity: 1.05 - 1.15

Product Function

TRUZAN DS – L is unique polymer when compared to most other polymers in oilfield drilling and completion application. Liquid Xanthan gums are well known for their ability to provide extremely low solids fluids with excellent carrying and suspending characteristics. Fluids thickened with liquid Xanthan gum have a tendency to thin at higher velocities and thicken at lower velocities.

Recommended Treatment

The effective concentration of TRUZAN DS – L required will depend upon the base fluid being treated. 2.4 liters of TRUZAN DS – L is equivalent to 1.0 kg of Dry Xanthan gum powder.

Standard Packing

TRUZAN DS – L is packaged in net weight of 18kgs/5 gal pail of product or 1150kgs/275 gal IBC other packaging options are available.

+971 2 610 7000
info@ppc.ae | www.ppc.ae
Abu Dhabi | UAE



Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.