

## TRUZAN

P1409.9307

WBM Drilling

### Product Description

TRUZAN is a polysaccharide (xanthan gum) used to viscosify water based drilling and completion fluids.

### Features and Benefits

TRUZAN provides excellent suspension properties restricting the settlement of weighting agents and drilled cuttings. TRUZAN is shear thinning and promotes low bit viscosity needed to maximize penetration rates, and high annular viscosity to ensure effective hole cleaning. TRUZAN is stable over a wide pH range and is effective in saturated brines as well as fresh and sea water base drilling fluids. TRUZAN is non-damaging to formations and can be removed effectively by acids and oxidants.

### International Shipping References

Transportation of TRUZAN is not restricted by any regulatory agency.

### Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

### Typical Physical Properties

- Physical State: Solid
- Max Temperature: 300
- Reservoir Compatible: Both
- Category: Viscosifiers
- Sub Category: Xanthan Gum
- Product Tier: Regular
- SG value: 1.5
- pH (1% solution): 6 - 8
- Bulk Density Kg/m<sup>3</sup>: 650 - 800
- Appearance: Cream colour free flowing powder

### Product Function

TRUZAN is used in drilling and completion fluids to enhance their rheology, ensuring efficient hole cleaning and effective suspension properties.

### Recommended Treatment

The effective concentration of TRUZAN required will depend upon the base fluid being treated. Treatment levels are normally in the range of 0.25–2.0 lbs/bbl (0.7–5.71 kgs/m<sup>3</sup>)

### Standard Packing

TRUZAN is packaged in 25 kgs multiwall paper sack.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS  
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.